Introduction to PowerWorld Simulator: Interface and Common Tools



I5: Data Aggregation using Areas,Zones, Interfaces, Super Areas,Injection Groups



2001 South First Street Champaign, Illinois 61820 +1 (217) 384.6330 support@powerworld.com http://www.powerworld.com

Aggregation of Data



- Areas and Zones
- Interfaces
 - Flowgates, Cutplanes, and Paths can be defined as interfaces
- Nomograms
- Super Areas
- Injection Groups
- Substations
- Difference Flows to compare different cases
 - values in the case (loads, gen MW outputs, etc...)
 - Also compare the topology of the case

Area and Zone Records



- Area and Zone definitions are part of standard power system case text formats
- Each bus is assigned to exactly one area
- Each bus is assigned to exactly one zone
- Generators, Shunts, and Loads are normally assigned to the same area as their terminal bus
 - However, they may also be given their own area and zone designation

Area and Zone Layouts



- Areas and Zones do NOT have to be contiguous
- Zones are often "sub-areas", but this is NOT required. They can overlap as shown below
 - Areas (thick lines)
 - Zones (shaded/nonshaded)



 A single area may consist of multiple zones, while a single zone can include buses from multiple areas

What are Areas and Zones For?




- Areas and Zones
 - Provide summary data about a group of power system elements (total load, generation, losses, etc...)
 - Provide way to filter data (Area/Zone filters)
 - Limit Monitoring Settings for Area/Zone
 - Toggle settings for equivalencing, scaling, etc...
- Areas ONLY (control settings)
 - Ability to perform automatic generation control (AGC)
 - Ability to specify MW transfer between areas
 - Ability to toggle control settings across a group of elements
 - AGC, Generator AVR, Shunts, Transformers
 - Ability to enable OPF/SCOPF constraint enforcement

Assigning Area and Zone Designations




- To create a new Area or Zone
 - Open Model Explorer and choose Network
 Buses or open the Bus Dialog and assign an existing bus to a new Area/Zone number; OR
 - Select Insert... from the local menu (right-click) in Area Records or Zone Records; OR
 - Auxiliary files or Copy/Paste from Excel



Moving Bus Zones and Creating New Zones via the Zone Dialog






- Buses can be assigned individually to zones using the Bus dialog.
- Groups of buses can be moved to different zones using the Zone Information dialog.
- The Zone Information dialog is available by right-clicking on the zone name on the Zone Records display.

Edit Mode Zone Information Dialog






Then click to move the selected buses

Run Mode Zone Dialog





Interface Definition



- Interfaces are groupings of branches and sometimes other elements
- The sum of the flows on these elements can then be monitored in the analysis tools
- Common interfaces are the grouping of tie lines between areas, and groupings of lines between important parts of the system.
- Interfaces can be used to model several commonly described groupings of lines
 - Flowgates term used in the Eastern United States
 - Cut-Planes term used in the Western United States
 - Paths term used in the state of California
 - Nomograms Used throughout the industry


Interface Records



- Interface records can be used to show flows between areas and/or zones.
- Interface records showing area to area flows can be automatically inserted by
 - Open Model Explorer and choose Aggregations ->
 Interfaces to display interface records
 - Select Interface records → Auto Insert Interfaces
 from the local menu to display Auto Insertion of
 Interfaces Dialog

Interface Records






Defining Custom Interface Records



- Open Model Explorer and choose Aggregations


 Interfaces to view the Interface display.
- Right-click and select Insert to add a new interface.
- The Interface Dialog is shown.
- We'll set up an interface showing flow on two parallel lines.



Monitored Interface Dialog



- Change Interface Name: Top Export
- Modify Interface Limit A (MW): 400
- Click Insert New Element button to add a new Interface Element
 - Type: Line/Transformer
 - Near : 2 (Two)
 - Far: 6(Six) CKT 1
- Repeat For
 - Type: Line/Transf.
 - Near : 5 (Five)
 - Far : 7 (Seven) CKT 1




Interface Element Type



- Line/Transformer
 - Monitor the flows on a line (direction is important!)
- Area to Area, and Zone to Zone
 - Monitor the sum of the flows on all tie lines
- Line Open/Close Contingency
 - When defining these, it means that all monitoring on this interface is done after this Line Open/Close contingency
- DC Line
 - Monitor the flow on a DC Line
- Injection Group, Generator, Load
 - Monitor the output of a group of generators or loads
 - Allows you to put a limit on the sum of outputs
- MS Line
 - Monitor the flow on a multi-section line
- Interface
 - Monitor the flow/output of another interface
 - Be careful not to create circular references

Monitored Interface Dialog





Interface Element Weightings




- Right-click on the list of elements and choose
 Display/Column Options
- Add the columns Weighting and Pre-Weight Flow
- This allows your interface to monitor the weighted sum of flows instead of the pure sum
- This will be used extensively with Nomogram Definitions

Nomograms



 Nomograms allow definition of 2-dimensional limit spaces using 2 interfaces



Nomograms




- Open Model Explorer and choose Aggregations

 Nomograms to bring up a list of Nomograms
- Right-click and choose Insert... to bring up the Nomogram Dialog for adding a new Nomogram
- A nomogram is defined by
 - Interface A
 - Interface B
 - A set of breakpoints
 - Breakpoints MUST create a "convex" region
- Nomogram limits can be used in ATC, contingency analysis, and OPF/SCOPF

Nomogram Dialog






Nomogram Interfaces



 For each nomogram, Simulator creates a list of nomogram interfaces which are managed internally

- This is done by using element weightings based on Interface A, Interface B, and the Breakpoints
- "number of breakpoints minus 1" nomogram interfaces are made




- The "monitoring" will then occur for each nomogram interface level.
 - Everywhere you see references to interfaces you will now also see references to nomogram interfaces

Nomogram Interfaces



- Once you have defined a Nomogram, then the
 Aggregations
 Nomogram Records tab will have a
 second sub-tab that lists the Nomogram Interfaces
 - Note: you can not edit Nomogram Interfaces directly. You must modify the Nomogram itself instead
 - Nomogram Interfaces are identified by their Nomogram Name
 - Nomogram Segment



Area/Zone/Interface Oneline Graphics



- Oneline diagrams traditionally contain information regarding individual power system elements (buses, lines, generators, etc...)
- Simulator also allows you to create diagrams based off the aggregate data objects


Area Fields



- Area fields can be added to onelines to show a number of area fields.
- Area fields can also be used to specify base transactions.
- By default, area fields are linked to the area associated with the closest bus on the oneline.

Area Field Dialog





AGC Status can be toggled on the oneline

Area number 0 (zero) represents the whole system!


Area Field Example



- Add several area fields to the B7FLAT case
 - Area Name
 - Area MW Flow to Other Area (or case)
 - Scheduled Flow to Other Area
 - Load Schedule Multiplier
 - AGC Status

B7FLAT with Area Fields





Area, Zone, and Super Area Objects




- Separate oneline object types for Areas, Zones, and Super Areas
- On B7FLAT case
- From the File Menu, select New Oneline to make a new oneline
- Add area objects for each of three areas
- From the File Menu, select **Save Oneline** to save the oneline. Use b7flata for the name.
- Zone and Super Area objects are similar

B7FLATA Display



Right-click on object, then select **Information Dialog...** for the Area Display Options




Area or Zone Palette



- Similar to the Bus Palette, you can also bring up an Area or Zone Palette
 - On the **Draw** ribbon tab, select **Show** Insert Palette For → Zones (or Areas)





Interface Fields




- Several types of objects are used to display interface data on the oneline
 - Interface Objects: like transmission lines
 - Interface Fields: like line fields
 - Interface Pie Charts: like line flow pie charts

Auto Insertion of Interface Objects




- Interface objects can be auto inserted (just like line objects).
- In edit mode, from the **Draw** ribbon tab, select
 Auto Insert → Interfaces.
- Allows insertion of interfaces and pie charts.
- Interfaces are automatically anchored to area/zone objects.

Auto Insertion of Interface Objects



Select **OK** to auto insert the interface objects

With Interface/Area Fields




Super Areas



- Super areas are groupings of individual areas; analogous to an area being a grouping of individual buses
- Super areas can be used to control several areas together
- Open Model Explorer and choose Aggregations
 Super Areas to see the Super Area Records
 - Right-click and select Insert...
 - Super Area Dialog is displayed with default name assigned to the new super area


Super Area Dialog






Super Area Dialog





Super Area ED Control for B7Flat Case





Injection Groups



- Represents grouping of injections of power
 - Loads
 - Generators
 - Switched Shunts
 - Other Injection Groups (be careful of circular references)
- Useful for defining more specific groups of sources and sinks in many tools
 - Especially useful for ATC, PVQV tools; also for Sensitivities (PTDF, TLR, etc...)
 - Also useful for general reporting, e.g. make an aggregation of generators and show the sum of their output

Injection Groups



- Open Model Explorer and choose
 Aggregations → Injection Groups
 - Right-click, select Insert...
 - Injection Groups Dialog is displayed with default name assigned to the new injection group
 - Right-click in the Participation Points grid and Insert elements into the injection group or click Insert Points
- Auto Insertion also available from the local menu in Model Explorer

Injection Groups

Click to Add



Elements

already in


injection

group

the

Add loads, generators, shunts, or other injection groups

Elements available for adding



Choose how to determine the participation factor for each element

Injection Group Participation Points




- Injection Groups are made up of "Participation Points" which have two main attributes
 - Reference to a generator, load, switched shunt, or another injection group
 - Participation factor
 - Note: this participation factor is independent of the generator object's participation factor
- When you create a participation point, you can define the initial participation factor for the point using various methods.
 - This is depicted on the following slide

Injection Group Participation Points: Participation Factors



- For a generator, the choices for participation factor are shown to the right
 - Specify particular value
 - Use generator's participation factor
 - Base on positive reserve (Max Present MW)
 - All units will hit their maximum at same time
 - Base on negative reserve (Present Min)
 - All units will hit their minimum at same time
 - Base on MW capability (Max MW)
 - Use Custom Floating Point Field
- Recalculate Factors Dynamically
 - Normally the participation factor will only be calculated at this time.
 - Check this box to automatically recalculate the factors EVERY TIME they are used
 - This way, if you use the injection group with a different case or different system state it will still be what you intend.



Injection Group Display Objects




- You can also insert display objects which represent Injection Groups
- On the **Draw** ribbon tab, choose **Aggregation** → **Injection Group**
- Click on the oneline where you would like to place the injection group
- Display objects show the generation and load which exist inside the group



Substations



- Some substations in a power system have a large number of buses in them
 - Large power stations
 - Other important places in a power system
- Traditional Power System Cases do not have any reference to which "substation" a bus is inside.
- Simulator allows you to define this relationship and then create substation-based diagrams




Creating Substations



- To create a new Substation
 - Make sure you're in Edit Mode (for all methods)
 - Open Network


 Buses in the Model Explorer or open the Bus Dialog and assign an existing bus to a new Substation number; OR
 - Select Insert... from the local menu (right-click) in Substation Records; OR
 - Auxiliary files or Copy/Paste from Excel



Substation Display Objects



- You can also insert display objects which represent Substations
- From the **Draw** ribbon tab, choose **Aggregation** Substation
- Click on the oneline where you would like to place the injection group
- Note: You can also auto-insert transmission lines between Substation objects



Symbols indicates whether Generation, Load, or Shunts exist inside the substation

Difference Flows




- Simulator allows two different power system cases to be simultaneously loaded
 - Present Case
 - Base Case
- Difference flows allow viewing of either case or of the differences between the cases
- Changes in status are shown using OPEN/CLOSED fields (present case status listed first)

Difference Flows Dialog




- The Difference Flows dialog is used to control which case is being viewed.
- The Difference Flows dialog can be viewed by either
 - Difference Flows option on oneline local menu
 - Difference Flows on the Tools ribbon tab




Difference Flows Dialog





Load Increased by 20%






Difference Flows



All fields now show the difference between the present case and the base case



You can NOT change values in the difference mode!

Comparing Two Different Case Files




- Simulator only allows one case to be open at a time.
- When you open a case, all information about the previously opened case is removed, with one exception
 - The Difference flows information is kept
- Thus to compare two cases, you
 - Open case #1, and go to Run Mode
 - Open Difference Flows and choose Set Present as Base Case
 - Open case #2
 - Open Difference Flows and change to Difference Case

Topological Comparison of Cases



On the Tools ribbon tab, choose Difference Flows ->
 Present Topological Differences from Base Case ...



Columns show the number of new, removed elements

New: elements in the present case which are not in the base case

Removed: elements not in the present case which were in the base case


Both: element in the present case and the base case

Topological Differences: Elements Removed Tab

Tab provides a list of removed elements

Also provides a reason why they were not found

in the present case.



Blank Page